



**C.M. TECHNOLOGY**

Designed and Manufactured in Australia

## PRODUCT SHORTFORM

[www.cmtechnology.com.au](http://www.cmtechnology.com.au)







**Tel: + 61 2 9764 6550**

### **MODEL 1525BA 24 V to 12 V Battery Charger 20 Amps total load.**

#### Product Overview

The 1525BA is ideal for constantly charging an auxiliary 12V lead acid battery from a 24 V DC source. Applications include tail gate lifters, caravan batteries and marine auxiliary batteries. The charging circuit is voltage and current limited and cannot boil or overcharge the battery. The 1525BA automatically shuts down when the battery is fully charged, providing a small trickle charge. Fully spike protected and totally waterproof anodized construction for automotive and marine use.



-  Operates from 20 to 30 volts.
-  Cool running & small size ( 195 mm x 125 x 75). Fits anywhere.
-  Fully protected load output, isolates the load in 3/1000 second in the event of failure or overload, re-connecting automatically if it is just a spike. The ultimate in protection.
-  Fully waterproof with sealed cable glands.
-  Locking plugs and sockets with pre-wired tails supplied. Pre-drilled mounting holes.
-  12 months full warranty.



**A Caspian Technology Company**

all materials presented are trade mark and copyright protected by C.M. TECHNOLOGY Pty Ltd